

Order No. Model No.	500005736 REV36P-HB		
Notes:			

Section 10309 - Manufactured Electric Fireplaces

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Manufactured electric fireplaces.
- B. Accessories

1.2 RELATED SECTIONS

A. Section 06100 - Rough Carpentry: Wood framed rough opening and enclosure.

1.3 REFERENCES

- A. UL 2021
- B. CSA C22.2 No. 46-13

1.4 SUBMITTALS

- A. Submit under provisions of Section 01300.
- B. Product Data: Manufacturer's data sheets on each product to be used, including:
 - Preparation instructions and recommendations.
 - Storage and handling requirements and recommendations.
 - Installation methods.
- C. Manufacturer's Certificates: Certify products meet or exceed specified requirements.
- D. Manufacturer's warranty.

1.5 DELIVERY, STORAGE, AND HANDLING

- A. Store products in manufacturer's unopened packaging until ready for installation.
- B. Protect materials from exposure to moisture. Do not deliver until after wet work is complete and dry.

1.6 WARRANTY

A. Provide the manufacturer's 2-year limited warranty on electrical components.

PART 2 PRODUCTS

2.1 ACCEPTABLE MANUFACTURERS

- A. Pre-fabricated Electric Fireplace:
 - 1. Base: Dimplex Electric Fireplace Glen Dimplex Americas 1367 Industrial Road Cambridge ON N3H 4W3
 - 1-888-346-7539
 - www.dimplex.com
 - Substitutions not permitted
 - 3. Requests for substitutions will be considered in accordance with provisions of Section 01600.



Order No. Model No.	500005736 REV36P-HB		
Notes:			

Section 10309 - Manufactured Electric Fireplaces

2.2 ELECTRIC FIREPLACES

A. General:

- Provide all components and accessories required for a complete, functional unit.
- 2. UL or CSA listed.

B. Pre-fabricated Electric Fireplace:

- 1. Base Product:
 - a) Dimplex Built-in Electric Firebox
 - b) Material Number: 500005736
 - c) Model Number: REV36P-HB
 - d) Regulatory model number: 6909791600
- 2. Description: Revillusion 36" Portrait Built-in/Fireplace Insert Electric Firebox, Herringbone Brick with Glass and Plug Kit
- 3. Dimensions:
 - a) Width: 37-1/8" / 94.4 cmb) Height: 31" / 78.8 cmc) Depth: 12-1/8" / 30.7 cm
- 4. Framing Dimensions:
 - a) Width: 36-5/8" / 93.0 cmb) Height: 30-5/8" / 77.8 cmc) Depth: 12-1/2" / 31.8 cm
- 5. Weight:
 - a) Product: 101.86 lbs / 46.2 kgb) Packaged: 105.5 lbs / 47.9 kg
- 6. Electrical:
 - a) Volts: 120 / 208 / 240
 - b) Watts: 1,300 / 1,975 / 2,575
 - c) Flame Only Watts: 40
 - d) BTUs: 4,436 / 6,739 / 8,786
- 7. Venting: Non-venting
- 8. Operation: Flame only, flame and heat
- 9. Heating: Louver-less, fan-forced circulation
- 10. Liner: Steel
- 11. Standard features:
 - a) Self-trimming design with flange to finish rough openings



Order No. Model No.	500005736 REV36P-HB		
Notes:			

Section 10309 - Manufactured Electric Fireplaces

- b) Patented flame technology create brighter and more random flames
- c) Partially frosted acrylic panel highlights flame without any reflections
- d) Full Herringbone Brick surround, 270°
- e) Customizable firebox hues, mood lighting to adjust firebox light level
- f) Powerful heating capabilities use as part of primary heat plan
- g) Direct-wire capabilities 120V, 240/208V
- h) Built-in touch controls
- i) 36" Tempered Front Glass 500000742
- j) Plug Kit X-RBFPLUG

12. Control options:

- a) Multi-function remote control
- b) Built-in touch controls

PART 3 EXECUTION

3.1 INSPECTION

- A. Do not begin installation until substrates have been properly prepared.
- B. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding.
- C. Verify proper power supply and fuel source are available.

3.2 PREPARATION

- A. Clean surfaces thoroughly prior to installation.
- B. Prepare surfaces using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions.

3.3 INSTALLATION

- A. Install in accordance with manufacturer's instructions and requirements of authorities having jurisdiction.
- B. Use manufacturer's guidelines for minimum clearances to combustibles, walls, and finishes.
- C. Anchor all components firmly in position for long life under hard use.
- D. Upon completion of installation, visually inspect all exposed surfaces. Touch up scratches and abrasions with touch up paint recommended by the manufacturer; make imperfections invisible to the unaided eye from a distance of 5 feet (1.5 m).

3.4 PROTECTION

- A. Protect installed products until completion of project.
- B. Touch-up, repair or replace damaged products before Substantial Completion.




Order No. **500005736**Model No. **REV36P-HB**


Notes:

Section 10309 - Manufactured Electric Fireplaces

Framing Dimensions:


	REV36P-HB	
Α	12-1/2" (31.8 cm)	
В	36-5/8" (93.0 cm)	
С	30-5/8" (77.8 cm)	
D	30-1/4" (76.8 cm)	
Е	12-1/8" (30.7 cm)	
F	35-3/8" (89.8 cm)	
G	37-1/8" (94.4 cm)	
Н	27-1/4" (69.1 cm)	
I	31" (78.8 cm)	
J	60" (152.4 cm)	
K	42-1/2" (108.0 cm)	
L	42-1/2" (108.0 cm)	





- The Revillusion™ Electric Fireplace/ Fireplace Insert does not require any special venting.
- 2. To build the rough-in opening, follow the framing dimensions below.

NOTE: The materials used for the finished surround must be cut to precise dimensions (dimensions B & C) as the 1/4" (0.6 cm) self trimming flange is only to create a finished appearance.





Scan for more information on dimensions, accessories, technical details.

To view full series visit: dimplex.com

1-800-668-6663